

# THE PERFECT TUBING

For every part of your process



Tubing guide



# Contents

## **Choosing the right tube 04**

### **Biopharm 06**

Pumpsil® 08

PureWeld® XL 10

Bioprene® 12

GORE® STA-PURE Series PCS 14

GORE® STA-PURE Series PFL 16

Hygienic LoadSure® tubing elements 18

Fluid path kit for bioprocessing 20

### **Industrial 22**

Marprene® 24

Neoprene® 26

Maxthane® tubing elements 28

Industrial LoadSure® tubing elements 30

# Choosing the right tube

**The best way to select a tube is to decide which materials are chemically suitable, and best meet the physical demands of your application.**

## **For maximum tube life**

Use a large-bore tube at low speed

## **For maximum flow rate**

Use the largest tube at maximum speed

## **For maximum accuracy**

Use a small bore tube at high speed

## **Tubing performance and selection**

Watson-Marlow Fluid Technology Group is the only peristaltic pump manufacturer to make their own tubing. The characteristics of the pump, including suction lift, pressure, life, flow rate and efficiency are all largely determined by the tubing.

The results of using tubing from other suppliers are unpredictable. If you have any question about tube performance or the selection of tubing for a new application, we will always be pleased to give you the best possible advice. Full technical datasheets are available for each material in this brochure. The datasheet will also provide full part codes for ordering.

## **Checking with an immersion test**

Request a tube sample card if you would like to check chemical compatibility with any tubing material.

## **Chemical compatibility**

Chemical compatibility tables are available at [www.wmtubing.com](http://www.wmtubing.com) and from any Watson-Marlow distributor

## **Validation packs**

Comprehensive validation packs are available for Pumpsil, PureWeld XL, Bioprene and STA PURE PCS.





Photo courtesy of NIBRT

# Biopharm

Pumpsil®

PureWeld® XL

Bioprene®

GORE® STA-PURE Series PCS

GORE® STA-PURE Series PFL



Single-use biopharm tubing for accurate metering, transfer and filtration duties. Absolute traceability with laser-etched part number, lot number and use-by date. Fully documented biocompatibility and comprehensive validation pack.

#### **Pumpsil Typical Characteristics**

Colour/transparency	Translucent
Spallation	Low
Certification	USP Class VI, FDA regulations 21 CFR 177.2600 for food contact. eur.Ph. 6.5: 3.1.9
Sterilisation methods	gamma, autoclave, EtO
Operating temperature	-20C to 80C

#### **Sizes**

Available in 30 different bore sizes, five wall thicknesses and three coil lengths including bulk reels. See material datasheet for full range and ordering information.

# PureWeld® XL



Designed for secure, cost effective peristaltic pumping and transfer duties, PureWeld XL delivers longer pump life than leading TPE competitors.

PureWeld XL has excellent chemical resistance, making it suitable for a range of bioprocessing fluids.

## PureWeld XL Typical Characteristics

- Colour/transparency Opaque
- Spallation Very low
- Certification USP Class VI, raw material meets FDA regulations 21 CFR 177.1810 for food contact. USP<85>, USP<661>, USP<788>
- Sterilisation methods Gamma, autoclave, EtO
- Operating temperature -20C to 65C

## Sizes

Available in 13 different bore sizes, and four wall thicknesses. See material datasheet for full range and ordering information.



Bioprene tubing is USP Class VI and FDA compliant and suitable for biopharmaceutical and food applications. Bioprene's long peristaltic life ensures process security, reducing risks in critical cGMP applications. Bioprene demonstrates broad chemical compatibility.

Fully documented biocompatibility and comprehensive validation pack, including FDA drug Master File.

#### Bioprene Typical Characteristics

- |                         |  |
|-------------------------|--|
| • Colour/transparency   | Beige/opaque   |
| • Spallation            | Low  |
| • Certification         | USP Class VI, FDA regulations 21 CFR 177.2600 for contact with aqueous food and NSF listed |
| • Sterilisation methods | Gamma, autoclave, EtO, CiP, SiP  |
| • Operating temperature | 5C to 80C  |

#### Sizes

Available in 15 different bore sizes, five wall thicknesses and three coil lengths including bulk reels and LoadSure elements. See material datasheet for full range and ordering information.

# GORE® STA-PURE Series PCS



PTFE-reinforced silicone tubing which provides long term performance with repeatable accuracy, vital in pharmaceuticals and other high technology industries. Suitable for pressures up to 7 bar (100 psi) GORE STA-PURE PCS provides the longest available tube life with virtually no spallation.

Fully documented biocompatibility and comprehensive validation pack.

## STA-PURE Series PCS Typical Characteristics

- Colour/transparency      Off-white/opaque
- Spallation                      Very low
- Certification                  USP Class VI
- Sterilisation methods      Autoclave, CIP, SIP
- Operating temperature      -20C to 80C

## Sizes

Available in 20 different bore sizes, three wall thicknesses and three element lengths. See material datasheet for full range and ordering information.



# GORE® STA-PURE Series PFL



PTFE-reinforced fluoroelastomer tubing which handles nearly all aggressive chemicals, including organic solvents such as methyl ethyl ketone, toluene and acetone. With 50 times longer life than other fluoroelastomers and pressures up to 4 bar.

## STA-PURE Series PFL Typical Characteristics

- Colour/transparency Off-white/opaque
- Spallation Very low
- Certification USP Class Vi, ISO 10993-1
- Sterilisation methods Autoclave, CiP, SiP
- Operating temperature -20C to 80C

## Sizes

Available in 20 different bore sizes, three wall thicknesses and three element lengths. See material datasheet for full range and ordering information.

# Hygienic LoadSure® tubing elements



When you need a pump with positive connection points and error-free tubing loading, choose Watson-Marlow LoadSure tube elements.

## **530 series pumps**

LoadSure tube elements are available as high pressure up to 7 bar, medium pressure up to 4 bar and low pressure up to 2 bar. All elements use Tri-clamp style PVDF connectors. The element connectors are colour coded to match the correct pumphead. element materials include Bioprene and STA-PURE PCS for high pressure, Bioprene, STA-PURE PCS and STA-PURE PFL for medium pressure, Bioprene, STA-PURE PCS and STA-PURE PFL and Pumpsil for low pressure.

## **630 series pumps**

LoadSure tube elements are available in two bore sizes of 12 mm and 17 mm and for medium pressures up to 4 bar or low pressure up to 2 bar. All elements use Tri-clamp style connectors. element materials include Bioprene and STA-PURE PCS for medium pressure and bioprene, Pumpsil and STA-PURE PFL for low pressure.

## **730 series pumps**


LoadSure tube elements are available in four bore sizes of 12.7 mm, 15.9 mm, 19.0 mm and 25.4 mm, for pressures up to 2 bar and use Tri-clamp style connectors. element materials include Bioprene, Pumpsil and STA-PURE PCS.

Consult Watson-Marlow for options on installation and interfacing pipework and fittings.

# Fluid path kit for bioprocessing

## BioBarb™

- Enhanced Tri-Clamp design reduces turbulence, allows complete drainage and reduces the risk of a seal failure
- puresu® assemblies use Oetiker clamps for a 360° radial seal
- Platinum-cured silicone tubing optimised for post gamma performance
- Excellent flow stability and low spallation during perisaltic pump applications
- High purity tubing with low extractible profile



## PureWeld® XL

- Delivers longer pump life than leading TPE competitors
- Sealable/weldable sterile connectivity
- Excellent chemical resistance

## BioPure gaskets

- Platinum-cured silicone delivers high purity and low extractables
- Flanged and unflanged size options
- Lot number laser etching available for traceability

## Q-Clamp

- Quick, easy, secure clamping system with tamper-evident identification
- ½ to 1½" sanitary connection and universal geometry compatible



# Industrial

Marprene®  
Neoprene®  
Maxthane® tubing elements  
Industrial LoadSure® tubing elements



A long life thermoplastic elastomer with resistance to a wide range of chemicals. Marprene is highly resistant to oxidising agents such as ozone, peroxides and sodium hypochlorite.

### Marprene Typical Characteristics

- Colour/transparency      Beige/opaque
- Spallation                      Fair
- Standards                      FDA regulations 21 CFR 177.2600 for contact with aqueous food.
- Operating temperature      5C to 80C

### Sizes

Available in thirty different bore sizes, five wall thicknesses and three coil lengths, including bulk reels which provide cost savings. Also suitable in Loadsure elements. See material datasheet for full range and ordering information.



Neoprene offers good performance with abrasive slurries in industrial applications. Good suction and pressure capabilities.

### Neoprene Typical Characteristics

- Colour Black
- Operating temperature 0C to 80C

### Sizes

Available in 18 different bore sizes, three different wall thicknesses and two coil lengths. See material datasheet for full range and ordering information.

# Maxthane<sup>®</sup> tubing elements



Maxthane is the perfect choice for peristaltic dosing and metering applications. The tubing is compatible with a broad range of chemicals. The long service life of Maxthane tubing makes it ideal for flavour, colour and additive dosing in food manufacturing.

Fully recyclable thermoplastic polyurethane construction achieves high-performance pumping with reduced environmental impact. Use Maxthane with 505LT and 520RET pumpheads.

## Size and format options

### LoadSure<sup>®</sup> Elements

3.2 mm  
6.4 mm  
9.6 mm

### Y- Elements

3.2 mm  
6.4 mm  
8.0 mm  
9.6 mm

## Food and beverage compliance

- FDA regulations 21 CFR 177.1680
- EC1935/2004, EU 10/2011



# Industrial LoadSure® tubing elements



When you need a pump with positive connection points and error-free tubing loading, choose Watson-Marlow LoadSure tube elements.

## **530 series pumps**

LoadSure tube elements are available as high pressure up to 7 bar, medium pressure up to 4 bar and low pressure up to 2 bar. All elements use quick-release PVDF connectors. The element connectors are colour coded to match the correct pumphead. Element materials include Maxthane for pressures up to 7 bar, Marprene, Pumpsil and Neoprene.

## **630 series pumps**

LoadSure tube elements are available in two bore sizes of 12 mm and 17 mm and for medium pressures up to 4 bar or low pressure up to 2 bar. All elements use industrial PVDF Cam and groove connectors. Element materials include Marprene for medium pressure and Marprene, Pumpsil and Neoprene for low pressure.

## **730 series pumps**

LoadSure tube elements are available in four bore sizes of 12.7 mm, 15.9 mm, 19.0 mm and 25.4 mm, for pressures up to 2 bar and use industrial PVDF Cam and groove connectors. Element materials include Marprene, Pumpsil and Neoprene.





Fluid Technology Group

INNOVATION IN FULL FLOW



## Watson-Marlow Fluid Technology Group

Watson-Marlow Fluid Technology Group supports its customers locally through an extensive global network of direct sales operations and distributors

[wmftg.com/global](http://wmftg.com/global)



Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains and reserves the right to alter specifications without notice. It is the users' responsibility to ensure product suitability for use within their application. Watson-Marlow, LoadSure, Qdos, ReNu, LaserTraceability, Pumpsil, PureWeld XL, Bioprene, Marprene, Accusil, asepticisu and puresu are registered trademarks of Watson-Marlow Limited. Bio Y, BioClamp, BioBarb, FlatBioEndCap, BioEndCap, BioValve and BioTube applicator are trademarks of BioPure Technology Limited. Tri-Clamp is a registered trademark of Alfa Laval Corporate AB. GORE and STA-PURE are trademarks of W.L. Gore and Associates.

A Spirax-Sarco Engineering plc company